

Uso de las hélices, consumos y potencias del motor Z2205-34 Para más información visite www.aero-import.com

HP-Z2205-34					
Fuente potencia	Hélice	Voltios	Amperios	RPM	Wattios
600W PS	APC7x5SF	6.7	8.1	8565	54
		7.7	10.1	9360	77
	APC8x3.8SF	6.7	10.3	7560	69
		GR7.5x4 Fold	6.7	8.4	8340
		7.7	10.5	9150	80
		ET-HPV2-0700-2S	APC7x5SF	6.65	7.8
ET-HPV2-1250-2S	APC7x5SF	7.04	8.6	8880	60
600W PS	APC5.1x4.5 E	6.7	4.6	9540	31
		7.7	5.5	10740	42
		8.8	6.7	11970	59
		9.9	8.2	12990	81
		10.1	8.6	13200	87
		11	9.6	14190	105
	APC6x4 E	6.7	4.3	9570	29
		7.7	5.4	10830	42
		8.8	6.7	12120	59
		9.9	7.9	13260	78
		10.1	8.2	13440	83
		11	9.3	14280	102
	GR6x3 Fold	6.7	5.3	9060	36
		7.7	6.5	10230	50
		8.8	7.9	11310	70
		9.9	9.6	12270	95
		10.1	9.9	12510	100
		ET-HPV2-0700-2S	APC7x5SF	6.51	7.2
ET-HPV2-1250-2S	APC7x5SF	6.95	8	8610	56