

Uso de las hélices, consumos y potencias del motor Z3013-16 Para más información visite www.aero-import.com

HP-Z3013-16				
Hélice	Voltios	Amperios	RPM	Wattios
APC8x6 E	6.7	7.6	6030	51
	7.7	9.1	6840	70
	8.8	11.5	7755	101
	9.9	13.9	8595	138
	10.1	14.3	8700	144
	11.0	17.0	9360	187
	12.1	20.0	10140	242
	13.2	23.6	10920	312
APC9x6 E	13.4	24.0	11010	322
	6.7	8.6	5880	58
	7.7	10.7	6690	82
	8.8	13.3	7545	117
	9.9	15.9	8400	157
	10.1	16.6	8580	168
	11.0	18.9	9180	208
	12.1	21.9	9960	265
APC10x5 E	13.2	25.4	10680	335
	13.4	26.1	10830	350
	14.3	29.0	11430	415
	15.4	32.2	12090	496
	6.7	9.1	5910	61
	7.7	11.5	6660	89
	8.8	14.4	7515	127
	9.9	17.3	8265	171
APC10x5 E	10.1	18.0	8370	182
	11.0	21.0	9060	231
	12.1	24.6	9690	298

	13.2	28.5	10440	376
	13.4	29.1	10500	390
	14.3	32.9	11040	470
	15.4	36.8	11610	567
APC11x5.5 E	6.7	12.0	5730	80
	7.7	14.7	6390	113
	8.8	18.4	7155	162
	9.9	22.3	7890	221
	10.1	23.5	7980	237
	11.0	27.0	8565	297
	12.1	31.7	9120	384
	13.2	36.7	9810	484
	13.4	36.9	9780	494
APC12x6 E	6.7	14.9	5370	100
	7.7	19.5	6015	150
	8.8	23.7	6750	209
	9.9	28.8	7290	285
	10.1	29.3	7380	296
	11.0	33.7	7845	371
	12.1	38.6	8370	467
APC13x6.5 E	6.7	18.9	5160	127
	7.7	24.1	5655	186
	8.8	29.2	6225	257
	9.9	35.0	6720	347
	10.1	36.1	6810	365
	11.0	39.8	7125	438
APC14x7 E	6.7	23.2	4815	155
	7.7	28.6	5250	220
	8.8	35.1	5775	309