

Uso de las hélices, consumos y potencias del motor Z3019-10 Para más información visite www.aero-import.com

HP-Z3019-10					
Hélice	Voltios	Amperios	RPM	Wattios	
APC8X6 E	12.1	26.2	10980	317	
	13.2	30.7	11760	405	
	13.4	31.7	11940	425	
	14.3	35.4	12630	506	
	15.4	40.5	13260	624	
APC9x6 E	10.1	20.4	9180	206	
	11.0	23.8	9960	262	
	12.1	28.1	10800	340	
	13.2	32.8	11610	433	
	13.4	33.7	11820	452	
APC10x5 E	14.3	37.9	12480	542	
	8.8	18.5	8040	163	
	9.9	22.4	8940	222	
	10.1	23.3	9090	235	
	11.0	27.2	9750	299	
APC11x5.5 E	12.1	32.3	10590	391	
	13.2	37.9	11310	500	
	13.4	38.7	11460	519	
	8.8	23.8	7710	209	
	9.9	29.1	8655	288	
APC12x6 E	10.1	29.9	8670	302	
	11.0	35.5	9330	391	
	6.7	19.7	5722	132	
	7.7	24.4	6570	188	
	8.8	31.4	7335	276	
APC13x6.5 E	9.9	38.2	8055	378	
	10.1	39.5	8205	399	
	6.7	25.3	5595	170	
	7.7	32.2	6330	248	
	8.8	39.5	6900	348	
APC14x7 E	6.7	30.8	5325	206	
	7.7	39.2	5880	302	

